


EXCEPTIONAL DRIVE AXLE PERFORMANCE

There's power in these drive axle tires—maximum power. The popular TY517 drive tire delivers outstanding traction, long even wear and superior durability. STEM-2 technology enables this tough performer to stand up to destructive forces, resulting in multiple retreads and lower maintenance costs.

28/32" Rib-Block Tread Depth


Delivers long wear and road-grabbing power for the long haul without any compromises in traction.



28/32" Tread Depth

Tapered Center Groove

This center-shaped groove promotes stone ejection and reduces tread-stone damage for enhanced casing life and retreadability.



Tapered Center Groove

Solid Outer Shoulder


Strong, durable, solid shoulder block ensures flat, even wear on all types of 2- and 3-axle tractors and trucks.



Solid Outer Shoulder

Three Large Circumferential Grooves

Extra wide, self-cleaning, V-shaped grooves for improved water dispersion, lateral stability and long, even wear.



Three Large Circumferential Grooves

Mud and Snow Rated for drive power in the toughest of conditions.

STEM-2 Technology for extended casing life, extended retread life, and extended durability.

Rock-Ejecting, Center-Groove Platform enhances casing life and retreadability by minimizing damage to the casing.

PURE YOKOHAMA TECHNOLOGY

TY517 is equipped with the best Yokohama premium design concepts to meet stringent, modern fleet performance demands.



Our STEM-2 technology extends the life of the casing by redirecting normally destructive stress forces.



TY517

SPECIFICATIONS

Tire Size	Ply Rating (L.R.)	Rim Size		Inflated Dimensions			Loaded Dimensions			Part #
		Meas.	Alt	Overall Width (Inch)	Overall Diameter (Inch)	Groove Depth (1/32")	Section Width (Inch)	Static Radius (Inch)	Rev/Mile	
295/75R22.5	14G	9.00	8.25	11.4	40.7	28	12.4	19.1	512	51701
295/75R22.5	16H	9.00	8.25	11.4	40.7	28	12.4	19.1	512	51721
11R22.5	14G	8.25	7.50	11.1	42.0	28	12.0	19.6	497	51702
11R22.5	16H	8.25	7.50	11.1	42.0	28	12.0	19.6	497	51722
285/75R24.5	14G	8.25	...	10.9	42.0	28	11.9	19.7	495	51703
11R24.5	14G	8.25	7.50	11.1	44.0	28	12.2	20.6	474	51704
11R24.5	16H	8.25	7.50	11.1	44.0	28	12.2	20.6	474	51724

Yokohama tires are subject to an ongoing development process. Yokohama Tire Corporation reserves the right to change product specifications at any time without notice or obligation. Not all models and sizes available in all locations.

Corporate Headquarters
 P.O. Box 4550
 Fullerton, California 92834-4550
 800.423.4544
 714.870.3800

Commercial Customer Service
 For Dealer Orders Call: 800.241.7051
 Dealer Fax Orders: 800.455.9656
 770.932.0560

Consumer Affairs
 800.722.9888

Remember to register your Yokohama tires either on-line at yokohamatire.com or by mail. Mail-in registration cards are available at authorized Yokohama dealers.



www.yokohamatire.com

M-332-0507